

ALABASTER GLOBE

Φ57 Engine

Mini-Trim Alabaster Globe Downlight



CUTOUT :57mm

Accessories can be ordered separately

Light Engine




SKU : EN-57

Mini-Trim




SKU : BZ-57

Alabaster Globe Baffle



SKU : BF-57-AG



Standard



Black
Painted
9005



White
Painted
9016

Curated Finishes (MOQ 20 applies)



Bright
Chrome



Regency
Champagne



Antique
Copper




Antique
Brass



Dark
Brass

IP Rating:	IP65 front
Optics:	120°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W
Ambient temp:	-20 °C to 25 °C
Class:	III
Ceiling Thickness:	9mm-28mm
Material:	Fine Aluminium 6063A + Alabaster Stone
Certifications:	CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, 60-MININUT FIRE RESISTANCE,CCC,BIS



10W Ra98 3000K 120°

h(m)	E(lx)	D(m)
0.5	52	1.20
1.0	13	2.40
1.5	6	3.60
2.0	3	4.80



Code example:

AFL 57 10W-AG -30 N 120-W

AFL/ adjustable

57 / cutout 57mm

10W / system power

AG / Alabaster Globe

30 / 3000K

N / non dim

120 / beam angle 120°

W/ white bezel



W system	lm system	optics	code
6W	182	120°	AFL5706W-AG-30N120
8W	235	120°	AFL5708W-AG-30N120
10W	286	120°	AFL5710W-AG-30N120