

ALABASTER GLOBE


Φ68 Engine

Mini-Trim Alabaster Globe Downlight



Accessories can be ordered separately

Light Engine





SKU : EN-68

Mini-Trim




SKU : BZ-68

Alabaster Globe Baffle



SKU : BF-68-AG



Standard



Curated Finishes (MOQ 20 applies)



- IP Rating:

Optics:

UGR:

CRI/RF/RG/R9:

Lifetime:

CCT:

Typical Source Efficacy (lm/W):

Control:

Binning

Input:

Output:

Ambient temp:

Class:

Ceiling Thickness:

Material:

Certifications:
- IP65 front

120°

<10

typ. 98/95/104/97

50,000 hrs (L90 B10)

2700K / 3000K / 3500K / 4000K / 2700K-6000K

110

On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi

2 Step MacAdams

AC220-240V 50/60Hz

DC 36V 200mA 8W

DC 36V 250mA 10W

DC 36V 300mA 12W


-20 °C to 25 °C

III

9mm-28mm

Fine Aluminium 6063A + Alabaster Stone

CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, 60-MININUT FIRE RESISTANCE,CCC,BIS



12W Ra98 3000K 120°

h(m)	E(lx)	D(m)
0.5	59	1.24
1.0	15	2.48
1.5	7	3.72
2.0	4	4.96



Code example:

AFL 68 12W-AG -30 N 120-W

AFL/ adjustable

68 / cutout 68mm

12W / system power


AG / Alabaster Globe

30 / 3000K

N / non dim

120 / beam angle 120°

W/ white bezel



W system	lm system	optics	code
8W	235	120°	AFL6808W-AG-30N120
10W	286	120°	AFL6810W-AG-30N120
12W	337	120°	AFL6812W-AG-30N120