

ALABASTER LUNA

Φ57 Engine


Mini-Trim Alabaster Luna Downlight



CUTOUT :57mm


Accessories can be ordered separately

Light Engine



SKU : EN-57

Mini-Trim





SKU : BZ-57


Alabaster Luna Baffle



SKU : BF-57-AL



Standard



Curated Finishes (MOQ 20 applies)



IP Rating:	IP65 front
Optics:	120°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K

Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W


Ambient temp: -20 °C to 25 °C

Class: III

Ceiling Thickness: 9mm-28mm

Material: Fine Aluminium 6063A + Alabaster Stone

Certifications: CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, 60-MININUT FIRE RESISTANCE,CCC,BIS



10W Ra98 3000K 120°

h(m)	E(lx)	D(m)
0.5	9	1.61
1.0	2	3.23
1.5	1	4.84



Code example:

AFL 57 10W-AL -30 N 120-W

AFL/ adjustable

57 / cutout 57mm

10W / system power



AL / Alabaster Luna

30 / 3000K

N / non dim

120 / beam angle 120°

W/ white bezel



W system	lm system	optics	code
6W	82	120°	AFL5706W-AL-30N120
8W	105	120°	AFL5708W-AL-30N120
10W	128	120°	AFL5710W-AL-30N120