


BELLA PRO 48V

Φ41


Adjustable 48V Track Light



Adjustable Optic



minimal track



standard track



Standard



Black
Painted
9005



White
Painted
9016

Curated Finishes (MOQ 20 applies)



Bright
Chrome



Regency
Champagne



Antique
Copper




Antique
Brass




Dark
Brass

IP Rating:	IP20
Optics:	15°/30°/40°/55°
UGR:	<17
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K/3000K/3500K/2700-6000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, 0/1-10V, Dali, Zigbee, Casambi
Binning:	2 Step MacAdams
Input:	48 VDC
Output:	DC 36V 150mA 6W
Ambient temp:	-20 °C to 25 °C
Class:	III
Material:	structure fine aluminum 6063A
Optional Accessories:	Honeycomb, Elliptical Lens, Solite lens




6W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	4391	0.14
1.0	1098	0.27
1.5	488	0.41
2.0	274	0.55
2.5	176	0.68
3.0	122	0.82




6W Ra98 3000K 30°

h(m)	E(lx)	D(m)
0.5	2085	0.28
1.0	521	0.55
1.5	232	0.83
2.0	130	1.10
2.5	83	1.38
3.0	58	1.65



6W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	1572	0.38
1.0	393	0.76
1.5	175	1.15
2.0	98	1.53
2.5	63	1.91
3.0	44	2.29



6W Ra98 3000K 55°

h(m)	E(lx)	D(m)
0.5	707	0.53
1.0	177	1.07
1.5	79	1.60
2.0	44	2.14
2.5	28	2.67
3.0	20	3.20




Code example:

MT 41 06W -30 N 15- B

MT/ 48V track light
 41/ 41 diameter
 06W/ system power
 30/ 3000K
 N/ non dim
 15/ beam angle 15°
 B/ black structure



DuraGreen project:
 YELLOWKORNER Art Gallery



W system	lm system	optics	code
6W	267	15°	MT4106W-30N15-B
6W	353	30°	MT4106W-30N30-B
6W	430	40°	MT4106W-30N40-B
6W	415	55°	MT4106W-30N55-B