








BELLA

Φ41 Adjustable 220-240V~ Zoomable 20°-50° Track Light



- IP Rating:** IP20
- Optics:** Zoomable 20°-50°
- UGR:** <17
- CRI:** 92Ra
- Lifetime:** 50,000 hrs (L90 B10)
- CCT:** 2700K/3000K/3500K
- Typical Source**
- Efficacy (lm/W):** 96
- Control:** On/off, Phase Cut, 0/1-10V, Dali, Casambi
- Binning** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 12V 350mA 6W
- Ambient temp:** -20 C to 25 C
- Class:** II
- Material:** structure fine aluminum 6063A
- Suitable Tracks:** Global, A.A.G STUCCHI, Eutrac, PowerGEAR, ERCO
- Certifications:** CE

	h(m)	E(lx)	D(m)
 6W Ra92 3000K 20°	0.5	2355	0.20
	1.0	589	0.40
	1.5	262	0.59
	2.0	147	0.79
	2.5	94	0.99
	3.0	65	1.19
	h(m)	E(lx)	D(m)
 6W Ra92 3000K 30°	0.5	1378	0.29
	1.0	344	0.58
	1.5	153	0.88
	2.0	86	1.17
	2.5	55	1.46
	3.0	38	1.75
	h(m)	E(lx)	D(m)
 6W Ra92 3000K 50°	0.5	616	0.47
	1.0	154	0.95
	1.5	68	1.42
	2.0	38	1.90
	2.5	25	2.37
	3.0	17	2.85



Code example:

MATL 41 06W -30 N 2050- B

MATL/ 220V adjustable track light

41 / 41 engine

06W / system power

30 / 3000K

N / non dim

2050 / zoomable 20°-50°

B/ black structure



DuraGreen project:
Bravo Art Gallery



W system	lm system	optics	code
6W	292-296	20°- 50°	MATL4106W-30N2050