


ORBIT


Φ45 Adjustable 220-240V~ Track Light



Adjustable Optic




IP Rating:	IP20
Optics:	15°/24°/36°/50°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 250mA 10W
Ambient temp:	-20 °C to 25 °C
Class:	II
Optional accessories:	Honeycomb, Elliptical Lens, Solite lens
Suitable Tracks:	Global, A.A.G STUCCHI, Eutrac, PowerGEAR, ERCO
Certifications:	CE




10W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	8822	0.15
1.0	2206	0.30
1.5	980	0.45
2.0	551	0.60
2.5	353	0.76
3.0	245	0.91




10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	6615	0.23
1.0	1654	0.46
1.5	735	0.69
2.0	413	0.92
2.5	265	1.15
3.0	184	1.37



10W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	3458	0.32
1.0	864	0.65
1.5	384	0.97
2.0	216	1.29
2.5	138	1.61
3.0	96	1.94



10W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	2048	0.45
1.0	512	0.89
1.5	228	1.34
2.0	128	1.79
2.5	82	2.24
3.0	57	2.68



Code example:

MATL 45 10W -30 N 15- B
 MATL/ 220V adjustable track light
 45 / 45 engine
 10W / system power
 30 / 3000K
 N / non dim
 15/ beam angle 15°
 B/ black structure



DuraGreen project:
 Agresti Showroom



W system	lm system	optics	code
10W	501	15°	MATL4510W-30N15-B
10W	653	24°	MATL4510W-30N24-B
10W	692	36°	MATL4510W-30N36-B
10W	676	50°	MATL4510W-30N50-B