


ORBIT

Φ45

Adjustable 220-240V~ Contour Track Light




Adjustable Optic



Black Painted

IP Rating:	IP20
Optics:	Framing
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Casambi
Binning:	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 250mA 10W
Ambient temp:	-20 °C to 25 °C
Class:	II
Suitable Tracks:	Global, A.A.G STUCCHI, Eutrac, PowerGEAR, ERCO
Certifications:	CE



10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	3216	0.21
1.0	804	0.42
1.5	357	0.63
2.0	201	0.84
2.5	129	1.04
3.0	89	1.25



Code example:

MATLC 45 10W -30 N F- B

MATLC/ 220V adjustable contour track light

45 / 45 engine

10W / system power

30 / 3000K

N / non dim

F / Framing

B/ black structure



W system	lm system	code
10W	239	MATLC4510W-30NF