
GLAMO

Φ68
Adjustable 220-240V~ Contour Track Light



Adjustable Optic










Black
Painted
9005

Contour spotlight illuminiates art with defined beam

IP Rating:	IP20
Optics:	Framing
UGR:	<17
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Casambi
Binning:	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 250mA 10W
Ambient temp:	-20 ℃ to 25 ℃
Class:	II
Material:	structure fine aluminum 6063A
Suitable Tracks:	Global, A.A.G STUCCHI, Eutrac, PowerGEAR, ERCO
Certifications:	CE



10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	3216	0.21
1.0	804	0.42
1.5	357	0.63
2.0	201	0.84
2.5	129	1.04
3.0	89	1.25






DuraGreen project:
Illumination Showcase at Shenzhen Creative Week

Code example:

MATLC 68 10W -30 N F- B

MATLC/ 220V adjustable contour track light
68 / 68 engine
10W / system power
30 / 3000K
N / non dim
F / Framing
B/ black structure



W system	lm system	code
10W	239	MATLC6810W-30NF