


CAELIA ALABASTER LUNA

Φ54

Outdoor Garden Spike



Fixed Optic



Accessories not included



24V DC-DC Constant-Current Driver

Designed to connect DuraGreen constant-current luminaires with a 3-18V forward-voltage range to a 24V DC constant-voltage supply. Available in 350mA, 500mA and 700mA versions.



Black Painted



Bespoke

IP Rating:	IP65
Optics:	120°
UGR:	<17
CRI:	92Ra
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K (3000K on request)
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 3V 700mA 2.5W
Ambient temp:	-20 °C to 45 °C
Class:	III
Plug Type:	Plug & Play (2 pin) - male
Certifications:	CE



Code example:

OGB 54 2.5W -AL -30 N 120- B

OGB/ CAELIA garden spike

54/ 54 diameter

2.5W / system power


AL/ Alabaster Luna

30 / 3000K

N / non dim

120/ beam angle 120°

B/ Black



W system	lm system	optics	code
2.5W	41	120°	OGB542.5W-AL-30N120