

ACME CURVE

Φ57 Engine

Trimless Adjustable Round Downlight



CUTOUT :57mm



Adjustable Optic



Accessories can be ordered separately

Light Engine



SKU : EN-57

Trimless




SKU : BZ-57-TL

Curve Baffle



SKU : BF-57-C



Standard



Black
Painted
9005



White
Painted
9016

Curated Finishes (MOQ 20 applies)



Bright
Chrome



Regency
Champagne



Antique
Copper



Heritage
Brass



Dark
Brass

IP Rating:

IP65 front

Optics:

15°/24°/36°/50°

UGR:

<10

CRI:

92Ra

Lifetime:

50,000 hrs (L90 B10)

CCT:

2700K / 3000K

Typical Source

Efficacy (lm/W):

180

Control:

On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi

Binning

2 Step MacAdams

Input:

AC220-240V 50/60Hz

Output:

DC 36V 200mA 8W

Ambient temp:

-20 °C to 25 °C

Class:

III

Optional accessories:


Honeycomb, Elliptical Lens, Solite lens

Material:

Fine aluminium 6063A


Certifications:

CB, CE, RoHS, ERP, UKCA, GLOBAL MARK,
60-MINUTE FIRE RESISTANCE, CCC, BIS




8W Ra92 3000K 15°

h(m)	E(lx)	D(m)
0.5	15780	0.15
1.0	3945	0.31
1.5	1753	0.46
2.0	986	0.62
2.5	631	0.77
3.0	438	0.93




8W Ra92 3000K 24°

h(m)	E(lx)	D(m)
0.5	10038	0.21
1.0	2509	0.42
1.5	1115	0.63
2.0	627	0.84
2.5	402	1.05
3.0	279	1.26



8W Ra92 3000K 36°

h(m)	E(lx)	D(m)
0.5	4591	0.32
1.0	1148	0.63
1.5	510	0.95
2.0	287	1.27
2.5	184	1.59
3.0	128	1.90



8W Ra92 3000K 50°

h(m)	E(lx)	D(m)
0.5	1681	0.47
1.0	420	0.95
1.5	187	1.42
2.0	105	1.90
2.5	67	2.37
3.0	47	2.85




Code example:

AFL 57 08W- C -TL -H30 N 36-TB B H

AFL/ adjustable
 57 / cutout 57mm
 08W / system power
 C / curve baffle
 TL / trimless
 H / high efficiency
 30 / 3000K
 N / non dim
 36 / beam angle 36°
 TB / trimless bezel
 B / black baffle
 H/ Honeycomb (Optional)



DuraGreen project:
Luxury Home in North London



W system	lm system	optics	code
8W	816	15°	AFL5708W-C-TL-H30N15
8W	936	24°	AFL5708W-C-TL-H30N24
8W	888	36°	AFL5708W-C-TL-H30N36
8W	821	50°	AFL5708W-C-TL-H30N50