

ACME IN-OUT

Φ57 Engine


Trimless Adjustable In/out Spotlights



cutout :57mm



Adjustable Optic



Standard




Curated Finishes (MOQ 20 applies)




IP Rating:	IP44 front
Optics:	15°/24°/36°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
CCT on request:	High efficiency 3000K / 2200K / WD 1800K - 3000K TW 1800K - 3000K / TW 1800K - 4000K

Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 200mA 8W
Ambient temp:	-20 °C to 25 °C
Class:	III
Optional accessories:	Honeycomb, Elliptical Lens, Solite lens
Material:	Fine aluminium 6063A
Certifications:	CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, CCC, BIS




8W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	7550	0.11
1.0	1888	0.22
1.5	839	0.34
2.0	472	0.45
2.5	302	0.56
3.0	210	0.67



8W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	2868	0.24
1.0	717	0.49
1.5	319	0.73
2.0	179	0.98
2.5	115	1.22
3.0	80	1.46



8W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	2108	0.36
1.0	527	0.72
1.5	234	1.08
2.0	132	1.44
2.5	84	1.80
3.0	59	2.16



Code example:

AFL 57 08W-IO-TL-30 N 36-TB B H

AFL/ adjustable

57 / cutout 57mm

08W / system power

IO / In-out

TL / trimless

30 / 3000K

N / non dim

36 / beam angle 36°

TB / trimless bezel

B/ black structure

H/ Honeycomb (Optional)



DuraGreen project:
CO | Michelin Starred Restaurant



W system	lm system	optics	code
8W	328	15°	AFL5708W-IO-TL-30N15
8W	404	24°	AFL5708W-IO-TL-30N24
8W	499	36°	AFL5708W-IO-TL-30N36