


ALABASTER GLOBE

Φ57 Engine

Trimless Alabaster Globe Downlight




CUTOUT :57mm



Accessories can be ordered separately

Light Engine



SKU : EN-57

Trimless



SKU : BZ-57-TL



CUTOUT :57



Alabaster Globe Baffle




SKU : BF-57-AG

IP Rating:	IP65 front
Optics:	120°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
CCT on request:	High efficiency 3000K / 2200K / WD 1800K - 3000K TW 1800K -3000K / TW 1800K - 4000K

Typical Source

Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W

Ambient temp:	-20 °C to 25 °C
Class:	III
Material:	Fine Aluminium 6063A + Alabaster Stone
Certifications:	CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, 60-MININUT FIRE RESISTANCE,CCC,BIS



10W Ra98 3000K 120°

h(m)	E(lx)	D(m)
0.5	52	1.20
1.0	13	2.40
1.5	6	3.60
2.0	3	4.80



Code example:

AFL 57 10W-AG -TL -30 N 120-TB

AFL/ adjustable

57 / cutout 57mm

10W / system power

AG / Alabaster Globe


TL / trimless

30 / 3000K

N / non dim

120 / beam angle 120°

TB / trimless bezel



W system	lm system	optics	code
6W	182	120°	AFL5706W-AG-TL-30N120
8W	235	120°	AFL5708W-AG-TL-30N120
10W	286	120°	AFL5710W-AG-TL-30N120