



ALABASTER LUNA

Φ57 Engine

Trimless Alabaster Luna Downlight




CUTOUT :57mm



Accessories can be ordered separately

Light Engine



SKU : EN-57


Trimless



SKU : BZ-57-TL



CUTOUT :57



Alabaster Luna Baffle



SKU : BF-57-AL

IP Rating:

IP65 front

Optics:

120°

UGR:

<10

CRI/RF/RG/R9:

typ. 98/95/104/97

Lifetime:

50,000 hrs (L90 B10)

CCT:

2700K / 3000K / 3500K / 4000K / 2700K-6000K

CCT on request:

High efficiency 3000K / 2200K / WD 1800K - 3000K
TW 1800K - 3000K / TW 1800K - 4000K

Typical Source

Efficacy (lm/W):

110

Control:

On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi

Binning

2 Step MacAdams

Input:

AC220-240V 50/60Hz

Output:

DC 36V 150mA 6W
DC 36V 200mA 8W
DC 36V 250mA 10W

Ambient temp:

-20 °C to 25 °C

Class:


III

Material:

Fine Aluminium 6063A + Alabaster Stone

Certifications:

CB, CE, RoHS, ERP, UKCA, GLOBAL MARK,
60-MINUT FIRE RESISTANCE, CCC, BIS



10W Ra98 3000K 120°

h(m)	E(lx)	D(m)
0.5	9	1.61
1.0	2	3.23
1.5	1	4.84



Code example:

AFL 57 10W-AL -TL -30 N 120-TB

AFL/ adjustable

57 / cutout 57mm

10W / system power

AL / Alabaster Luna


TL / trimless

30 / 3000K

N / non dim

120 / beam angle 120°

TB / trimless bezel



W system	lm system	optics	code
6W	82	120°	AFL5706W-AL-TL-30N120
8W	105	120°	AFL5708W-AL-TL-30N120
10W	128	120°	AFL5710W-AL-TL-30N120