

BELLA SNOOT


Φ78 Engine Trimless Long Snoot Zoomable Downlight



cutout:78mm



Adjustable Optic



Standard




Curated Finishes (MOQ 20 applies)



- IP Rating:** IP44 front
- Optics:** Zoomable 20°-50°
- UGR:** <10
- CRI/RF/RG/R9:** typ. 98/95/104/97
- Lifetime:** 50,000 hrs (L90 B10)
- CCT:** 2700K / 3000K / 3500K / 4000K / 2700K-6000K
- CCT on request:** High efficiency 3000K / 2200K / WD 1800K - 3000K
TW 1800K - 3000K / TW 1800K - 4000K


Typical Source

- Efficacy (lm/W):** 110
- Control:** On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
- Binning** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 36V 250mA 10W
- Ambient temp:** -20 °C to 25 °C
- Class:** III
- Material:** Fine aluminium 6063A
- Certifications:** CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, CCC, BIS



10W Ra98 3000K 20°

h(m)	E(lx)	D(m)
0.5	4916	0.20
1.0	1229	0.40
1.5	546	0.59
2.0	307	0.79
2.5	197	0.99
3.0	137	1.19



10W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	1480	0.44
1.0	370	0.88
1.5	164	1.32
2.0	92	1.76
2.5	59	2.21
3.0	41	2.65



Code example:

AFL 78 10W- LS -30 N 2050-TB B

AFL/ adjustable

78 / cutout 78mm

10W / system power

LS / Long Snoot

TL / trimless

30 / 3000K

N / non dim

2050 / Zoomable 20°-50°

TB/ trimless bezel

B/ black baffle



W system	lm system	optics	code
10W	703-690	20°- 50°	AFL7810W-LS-TL-30N2050