

ACME WALL-WASHER

Φ110 Engine


Mini-Trim Wall Wash Downlight



CUTOUT :110mm



Wall Wash Optic




Standard



Black
Painted
9005



White
Painted
9016



X = distance to wall
= ceiling height ÷ 3

IP Rating:	IP44
Optics:	Asymmetrical Wallwash
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
CCT on request:	High efficiency 3000K / 2200K / WD 1800K - 3000K TW 1800K - 3000K / TW 1800K - 4000K

Typical Source

Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 700mA 30W
Ambient temp:	-20 °C to 25 °C
Class:	III
Ceiling Thickness:	9mm-28mm
Material:	Fine aluminium 6063A
Certifications:	CE,BIS



Code example:

MFL 110 30W-30 N WS-W B

MFL/ Fixed

110 / cutout 110mm

30W / system power

30 / 3000K

N / non dim

WS / Wallwash

W/ white bezel

B/ black baffle



W system	lm system	optics	code
30W	896	Asymmetrical Wallwash	MFL11030W-30NWS