

ACME WALL-WASHER

Φ68 Engine


Trimless Wall Wash Downlight




CUTOUT: 68mm



Wall Wash Optic



Standard



X = distance to wall
= ceiling height ÷ 3

IP Rating:	IP65 front
Optics:	Asymmetrical Wallwash
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
CCT on request:	High efficiency 3000K / 2200K / WD 1800K - 3000K TW 1800K-3000K / TW 1800K - 4000K

Typical Source

Efficacy (lm/W):

110

Control:

On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi

Binning

2 Step MacAdams

Input:

AC220-240V 50/60Hz

Output:

DC 36V 350mA 15W

Ambient temp:

-20 °C to 25 °C

Class:


III

Material:

Fine aluminium 6063A

Certifications:

CB, CE, RoHS, ERP, UKCA, GLOBAL MARK,
CCC, BIS



15W Ra98 3000K
Asymmetrical

h(m)	E(lx)	D(m)
0.5	50	0.82
1.0	12	1.64
1.5	6	2.46
2.0	3	3.27
2.5	2	4.09
3.0	1	4.91



Code example:

MFL 68 15W-TL- 30 N WS-TB B

MFL/ Fixed

68 / cutout 68mm

15W / system power

TL / trimless


30 / 3000K

N / non dim

WS / Wallwash

TB / trimless bezel

B/ black baffle



W system	lm system	optics	code
15W	448	Asymmetrical Wallwash	MFL6815W-TL-30NWS