


ACME ALABASTER STRATA SURFACE

Φ57 Engine Surface Fixed Light



Fixed Optic



Remote DALI Driver

Integrated On/off, Phase Cut, 0/1-10V Driver


Standard



Curated Finishes (MOQ 20 applies)




IP Rating:	IP65 front
Optics:	15°/24°/120°
UGR:	<17
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W
Ambient temp:	-20 °C to 25 °C
Class:	III
Material:	Fine Aluminium 6063A + Alabaster Stone
Certifications:	CE




10W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	13172	0.14
1.0	3293	0.28
1.5	1464	0.42
2.0	823	0.56
2.5	527	0.70
3.0	366	0.84



10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	7091	0.21
1.0	1773	0.43
1.5	788	0.64
2.0	443	0.86
2.5	284	1.07
3.0	197	1.29



10W Ra98 3000K 120°

h(m)	E(lx)	D(m)
0.5	52	1.20
1.0	13	2.40
1.5	6	3.60
2.0	3	4.80



Code example:

SFE 57 10W- AS -30 N 120-W

SF/ surface fixed

E57 / 57 engine

10W / system power

AS / Alabaster Strata

30 / 3000K

N / non dim

120 / beam angle 120°

W/ white structure



W system	lm system	optics	code
6W	450	15°	SFE5706W-AS-30N15
6W	532	24°	SFE5706W-AS-30N24
6W	182	120°	SFE5706W-AS-30N120



W system	lm system	optics	code
8W	582	15°	SFE5708W-AS-30N15
8W	624	24°	SFE5708W-AS-30N24
8W	235	120°	SFE5708W-AS-30N120



W system	lm system	optics	code
10W	704	15°	SFE5710W-AS-30N15
10W	751	24°	SFE5710W-AS-30N24
10W	286	120°	SFE5710W-AS-30N120