


ACME ALABASTER STRATA WALL

Φ57 Engine Wall Light



Fixed Optic



Standard




Bespoke



Integrated Driver

IP Rating:	IP65 front
Optics:	120°
UGR:	<17
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W*2 DC 36V 200mA 8W*2 DC 36V 250mA 10W*2
Ambient temp:	-20 °C to 25 °C
Class:	III
Material:	Fine Aluminium 6063A + Alabaster Stone



10W Ra98 3000K 120°

h(m)	E lx	D(m)
0.5	9	1.61
1.0	2	3.23
1.5	1	4.84



Code example:

W E57 10WX2 -AS -30 N 120- RC

W/ wall light

E57/ 57 engine

10WX2 / system power


AS / Alabaster Strata

30 / 3000K

N / non dim

120/ beam angle 120°

RC/ Regency Champagne structure



W system	lm system	optics	code
6W*2	82*2	120°	WE5706WX2-AS-30N120
8W*2	105*2	120°	WE5708WX2-AS-30N120
10W*2	128*2	120°	WE5710WX2-AS-30N120