GLAMO CONTOUR

Ø68
Surface Contour Spotlight



Adjustable Optic







Installation Accessories



Black Painted

IP Rating:	IP20
Optics:	Framing
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K/3000K/3500K/2700-6000K
Typical Source Efficacy (lm/W):	113
Control:	On/off, Phase Cut, 0/1-10V, Dali
Binning	2 Step MacAdams
Driver Input:	AC220-240V 50/60Hz
Electrical (System W):	DC 36V 250mA 10W
Ambient temp:	-20 ℃ to 25 ℃
Class:	II
Material:	Fine aluminium 6063A



Code example:

STC 68 10W -30 N 36-W B
STC/ surface contour
68 / 68 engine
10W / system power
30 / 3000K
N / non dim
36 / zoomable 36°
W/ white bezel **TB** / trimless bezel
B/ black structure



10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	3216	0.21
1.0	804	0.42
1.5	357	0.63
2.0	201	0.84
2.5	129	1.04
3.0	89	1.25



W system	lm system	code
10W	239	STC6810W-30NF