ACME STRAIGHT

Ø57 Engine

Trimless Adjustable Round Downlight



CUTOUT :57mm



Adjustable Optic



Accessories can be ordered separately

Light Engine



SKU：EN-57

Trimless



SKU： BZ-57-TL

Straight Baffle



SKU：BF-57





Standard



Black Painted 9005



White Painted 9016

Curated Finishes (MOQ 20 applies)



Regency Champagne



Heritage Brass



Bright Chrome



Black Nickel

IP Rating:	IP65 front
Optics:	15°/24°/36°/50°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
CCT on request:	High efficiency 3000K /2200K / WD 1800K - 3000K TW 1800K -3000K / TW 1800K - 4000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Driver Input:	AC220-240V 50/60Hz
Electrical (System W):	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W
Ambient temp:	-20 ℃ to 25 ℃
Class:	III
Optional accessories:	Honeycomb, Elliptical Lens, Solite lens
Material:	Fine aluminium 6063A
Certifications:	CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, 60-MINUTE FIRE RESISTANCE, CCC, BIS



10W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	13172	0.14
1.0	3293	0.28
1.5	1464	0.42
2.0	823	0.56
2.5	527	0.70
3.0	366	0.84



10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	7091	0.21
1.0	1773	0.43
1.5	788	0.64
2.0	443	0.86
2.5	284	1.07
3.0	197	1.29



10W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	3820	0.31
1.0	955	0.63
1.5	424	0.94
2.0	239	1.25
2.5	153	1.57
3.0	106	1.88



10W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	1678	0.50
1.0	420	1.01
1.5	186	1.51
2.0	105	2.01
2.5	67	2.51
3.0	47	3.02





Code example:

AFL 57 10W-TL -30 N 36-TB W H

AFL/ adjustable
57 / cutout 57mm
10W / system power
TL / trimless
30 / 3000K
N / non dim
36 / beam angle 36°
TB / trimless bezel
W / white baffle
H/ Honeycomb（Optional）



W system	lm system	optics	code
6W	450	15°	AFL5706W-TL-30N15
6W	532	24°	AFL5706W-TL-30N24
6W	523	36°	AFL5706W-TL-30N36
6W	464	50°	AFL5706W-TL-30N50



W system	lm system	optics	code
8W	582	15°	AFL5708W-TL-30N15
8W	624	24°	AFL5708W-TL-30N24
8W	661	36°	AFL5708W-TL-30N36
8W	600	50°	AFL5708W-TL-30N50



W system	lm system	optics	code
10W	704	15°	AFL5710W-TL-30N15
10W	751	24°	AFL5710W-TL-30N24
10W	814	36°	AFL5710W-TL-30N36
10W	723	50°	AFL5710W-TL-30N50