ARTFOCUS SURFACE


Ø36 Engine

Surface Spotlight




Adjustable Optic







Installation Accessories



Standard



Black Painted 9005




White Painted 9016




Bespoke

IP Rating:	IP20
Optics:	15°/28°/36°
UGR:	<17
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K/3000K/3500K/4000K
Typical Source Efficacy (lm/W):	133
Control:	On/off, Phase Cut, 0/1-10V, Dali
Binning	2 Step MacAdams
Driver Input:	AC220-240V 50/60Hz
Electrical (System W):	DC 36V 150mA 6W
Ambient temp:	-20 ˚C to 25 ˚C
Class:	III
Material:	Fine aluminium 6063A
Optional Accessories:	Honeycomb, Elliptical Lens, Solite lens
Certifications:	CE




6W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	4937	0.14
1.0	1234	0.27
1.5	549	0.41
2.0	309	0.54
2.5	197	0.68
3.0	137	0.81



6W Ra98 3000K 28°


h(m)	E(lx)	D(m)
0.5	2848	0.25
1.0	712	0.49
1.5	316	0.74
2.0	178	0.98
2.5	114	1.23
3.0	79	1.47



6W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	1706	0.31
1.0	426	0.62
1.5	190	0.93
2.0	107	1.25
2.5	68	1.56
3.0	47	1.87





Code example:

SA 36 06W (/SB) -30 N 15- BB
SA/ ARTFOCUS surface
36 / 36 engine
06W / system power
SB/ Standard Base
30 / 3000K
N / non dim
15/ beam angle 15°
B/black structure
B/ black baffle



W system	lm system	optics	code
6W	373	15°	SA3606W-30N15
6W	445	28°	SA3606W-30N28
6W	446	36°	SA3606W-30N36



W system	lm system	optics	code
6W	373	15°	SA3606W/SB-30N15
6W	445	28°	SA3606W/SB-30N28
6W	446	36°	SA3606W/SB-30N36