
ALABASTER GLOBE

Ø57 Engine

Trimless Alabaster Globe Downlight




CUTOUT :57mm





Accessories can be ordered separately


Light Engine



SKU：EN-57

Trimless






SKU： BZ-57-TL

Alabaster Globe Diffuser



SKU：BF-57-AG

IP Rating:	IP65 front
Optics:	120°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
CCT on request:	High efficiency 3000K /2200K / WD 1800K - 3000K TW 1800K -3000K / TW 1800K - 4000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Driver Input:	AC220-240V 50/60Hz
Electrical (System W):	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W
Ambient temp:	-20 ℃ to 25 ℃
Class:	III
Material:	Fine Aluminium 6063A + Alabaster Stone
Certifications:	CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, 60-MINUTE FIRE RESISTANCE, CCC, BIS



10W Ra98 3000K 120°


h(m)	E(lx)	D(m)
0.5	52	1.20
1.0	13	2.40
1.5	6	3.60
2.0	3	4.80





Code example:

AFL 57 10W-AG -TL -30 N 120-TB
AFL/ adjustable
57 / cutout 57mm
10W / system power
AG / Alabaster Globe
TL / trimless
30 / 3000K
N / non dim
120 / beam angle 120°
TB / trimless bezel



W system	lm system	optics	code
6W	182	120°	AFL5706W-AG-TL-30N120
8W	235	120°	AFL5708W-AG-TL-30N120
10W	286	120°	AFL5710W-AG-TL-30N120