
ALABASTER LUNA

Ø57 Engine


Mini-Trim Alabaster Luna Downlight



CUTOUT :57mm



Standard




Curated Finishes (MOQ 20 applies)






Accessories can be ordered separately

Light Engine



SKU： EN-57

Mini-Trim




SKU： BZ-57

Alabaster Luna Diffuser



SKU： BF-57-AL

IP Rating:	IP65 front
Optics:	120°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
CCT on request:	High efficiency 3000K /2200K / WD 1800K - 3000K TW 1800K -3000K / TW 1800K - 4000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Driver Input:	AC220-240V 50/60Hz
Electrical (System W):	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W
Ambient temp:	-20 ℃ to 25 ℃
Class:	III
Ceiling Thickness:	9mm-28mm
Material:	Fine Aluminium 6063A + Alabaster Stone
Certifications:	CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, 60-MINUTE FIRE RESISTANCE, CCC, BIS



10W Ra98 3000K 120°


h(m)	E(lx)	D(m)
0.5	9	1.61
1.0	2	3.23
1.5	1	4.84





Code example:

AFL 57 10W-AL -30 N 120-B
AFL/ adjustable
57 / cutout 57mm
10W / system power
AL / Alabaster Luna
30 / 3000K
N / non dim
120 / beam angle 120°
B/ black bezel



W system	lm system	optics	code
6W	82	120°	AFL5706W-AL-30N120
8W	105	120°	AFL5708W-AL-30N120
10W	128	120°	AFL5710W-AL-30N120