
ALABASTER STRATA

Ø57 Engine

Mini-Trim Alabaster Strata Downlight



CUTOUT :57mm



Standard

Black Painted 9005

White Painted 9016


Curated Finishes (MOQ 20 applies)

Regency Champagne

Heritage Brass


Bright Chrome

Black Nickel




Accessories can be ordered separately

Light Engine



SKU： EN-57

Mini-Trim




SKU： BZ-57

Alabaster Luna Diffuser




SKU： BF-57-AS

IP Rating:	IP65 front
Optics:	15°/24°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
CCT on request:	High efficiency 3000K /2200K / WD 1800K - 3000K TW 1800K -3000K / TW 1800K - 4000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Driver Input:	AC220-240V 50/60Hz
Electrical (System W):	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W
Ambient temp:	-20 ℃ to 25 ℃
Class:	III
Ceiling Thickness:	9mm-28mm
Material:	Fine Aluminium 6063A + Alabaster Stone
Certifications:	CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, 60-MINUTE FIRE RESISTANCE, CCC, BIS



10W Ra98 3000K 15°


h(m)	E(lx)	D(m)
0.5	13172	0.14
1.0	3293	0.28
1.5	1464	0.42
2.0	823	0.56
2.5	527	0.70
3.0	366	0.84



10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	7091	0.21
1.0	1773	0.43
1.5	788	0.64
2.0	443	0.86
2.5	284	1.07
3.0	197	1.29





Code example:

AFL 57 10W-AS -30 N 15-B
AFL/ adjustable
57 / cutout 57mm
10W / system power
AS / Alabaster Strata
30 / 3000K
N / non dim
15 / beam angle 15°
B/ black bezel



W system	lm system	optics	code
6W	450	15°	AFL5706W-AS-30N15
6W	532	24°	AFL5706W-AS-30N24



W system	lm system	optics	code
8W	582	15°	AFL5708W-AS-30N15
8W	624	24°	AFL5708W-AS-30N24



W system	lm system	optics	code
10W	704	15°	AFL5710W-AS-30N15
10W	751	24°	AFL5710W-AS-30N24