GLAMO ZOOM RECESSED


Ø68 Engine

Semi-Recessed Zoomable 15°-50° Spotlight




Adjustable Optic







Installation Accessories



Standard


Black Painted 9005

White Painted 9016




Bespoke

IP Rating:	IP20
Optics:	Zoomable 15°-50°
UGR:	<17
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning:	2 Step MacAdams
Driver Input:	AC220-240V 50/60Hz
Electrical (System W):	DC 36V 300mA 12W
Ambient temp:	-20 ℃ to 25 ℃
Class:	III
Material:	Fine aluminium 6063A
Certifications:	CE



12W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	12099	0.14
1.0	3025	0.27
1.5	1344	0.41
2.0	756	0.54
2.5	484	0.68
3.0	336	0.81



12W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	2174	0.38
1.0	544	0.76
1.5	242	1.14
2.0	136	1.52
2.5	87	1.90
3.0	60	2.28





DuraGreen project:
YELLOWKORNER Art Gallery

Code example:

RT 68 12W -30 N 1550-W B
RT/ mini-trim
TL/ trimless

68 / 68 engine
12W / system power
30 / 3000K
N / non dim
1550 / zoomable 15°-50°
W/ white bezel TB / trimless bezel
B/ black structure



W system	lm system	optics	code
6 W	437-433	15°- 50°	RT6806W-30N1550
8 W	623-544	15°- 50°	RT6808W-30N1550
10W	585-589	15°- 50°	RT6810W-30N1550
12W	756-747	15°- 50°	RT6812W-30N1550



W system	lm system	optics	code
6 W	437-433	15°- 50°	TL6806W-30N1550
8 W	623-544	15°- 50°	TL6808W-30N1550
10W	585-589	15°- 50°	TL6810W-30N1550
12W	756-747	15°- 50°	TL6812W-30N1550