

Black Matt



White Matt



Silver Matt



Black Specular




Silver Specular



Gold Specular



Grey Specular



Specification Code

Type	Cut out	Power	Colour Temp	Driver	Beam Width		Bezel Colour	Baffle Colour	Options
MF	**75**	**08W**	**30**	**N**	**24**	**-**	**W**	**B**	**C**
MF/Fixed AF/Adjustable MFL/Lens type, Fixed AFL/Lens type, Adjustable MFW/Wall Wash MFZ/Zoomable MFP/Pinhole MFQ/Fixed Square	55/55mm 60/58mm 75/75mm 80/80mm 100/100mm		22/2200K 27/2700K 30/3000K 35/3500K 40/4000K 2760/2700K-6000K 22/2200K 1830/1800K - 3000K 1840/1800K - 4000K	P/Phase Cut D/DALI 0/0-10V Z/Zigbee C/Casambi N/Non Dim X/No Driver	05/5° 10/10° 13/13° 15/15° 20/20° 24/24° 30/30° 36/36° 50/50° 55/55° WS/Wall Wash		W/White B/Black PC/Polished Chrome PB/Polished Brass AB/Antique Bronze SN/Satin Nickel	B/Black Matt W/White Matt SM/Silver Matt GRS/Grey Specular BS/Black Specular SS/Silver Specular GOS/Gold Specular	C/Clear Lens F/Frosted Lens H/Honeycomb S/Spread Lens

MOOD


Ø75
Mini-Trim Fixed Round Downlight



CUTOUT :75mm



Fixed Optic





bezel



Black



White

baffle



Black Matt



White Matt



Silver Matt



Grey Specular



Black Specular



Silver Specular




Gold Specular




Bespoke

IP Rating:	IP20 and IP44 options
Optics:	24°/36°/50°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
CCT on request:	High efficiency 3000K /2200K / WD 1800K - 3000K TW 1800K -3000K / TW 1800K - 4000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Driver Input:	AC220-240V 50/60Hz
Electrical (System W):	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W DC 36V 300mA 12W
Ambient temp:	-20 ℃ to 25 ℃
Class:	III
Optional accessories:	Honeycomb, Elliptical Lens, Solite lens
Material:	Fine aluminium 6063A
Certifications:	CB, CE, RoHS, UKCA, GLOBAL MARK, CCC




12W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	8941	0.21
1.0	2235	0.43
1.5	993	0.64
2.0	559	0.85
2.5	358	1.06
3.0	248	1.28



12W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	4622	0.32
1.0	1156	0.64
1.5	514	0.96
2.0	289	1.28
2.5	185	1.61
3.0	128	1.93



12W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	1641	0.46
1.0	410	0.92
1.5	182	1.39
2.0	103	1.85
2.5	66	2.31
3.0	46	2.77







DuraGreen project:
Alacarte Halong Bay Condotel

Code example:


MFL 75 12W-30 N 36-W B H
MFL/ fixed
75 / cutout 75mm
12W / system power
30 / 3000K
N / non dim
36 / beam angle 36°
W/ white bezel
B/ black baffle
H/ Honeycomb（Optional）




W system	lm system	optics	code
6W	593	24°	MF7506W-30N24
6W	590	36°	MF7506W-30N36
6W	617	50°	MF7506W-30N50



W system	lm system	optics	code
8W	787	24°	MF7508W-30N24
8W	785	36°	MF7508W-30N36
8W	820	50°	MF7508W-30N50



W system	lm system	optics	code
10W	971	24°	MF7510W-30N24
10W	952	36°	MF7510W-30N36
10W	994	50°	MF7510W-30N50



W system	lm system	optics	code
12W	1097	24°	MF7512W-30N24
12W	1103	36°	MF7512W-30N36
12W	1108	50°	MF7512W-30N50