ACME WALL-WASHER

Ø110 Engine

Trimless Wall Wash Downlight



CUTOUT :110mm



Wall Wash Optic





Standard



Black Painted 9005

White Painted 9016



X = distance to wall
= ceiling height ÷ 3

IP Rating:	IP44
Optics:	Asymmetrical Wallwash
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
CCT on request:	High efficiency 3000K /2200K / WD 1800K - 3000K TW 1800K -3000K / TW 1800K - 4000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Driver Input:	AC220-240V 50/60Hz
Electrical (System W):	DC 36V 600mA 25W
Ambient temp:	-20 ˚C to 25 ˚C
Class:	III
Material:	Fine aluminium 6063A
Certifications:	CE, BIS





25W Ra92 3000K
Asymmetrical

h(m)	E(lx)	D(m)
1.0	406	0.81
2.0	101	1.62
3.0	45	2.43
4.0	25	3.25
5.0	16	4.06
6.0	11	4.87

Code example:

MFL 110 25W-TL- 30 N WS-TB W
MFL/ Fixed
110 / cutout 110mm
25W / system power
TL / trimless
30 / 3000K
N / non dim
WS / Wallwash
TB / trimless bezel
W/ white baffle



W system	lm system	optics	code
25W	1222	Asymmetrical Wallwash	MFL11025W-TL-30NWS