PIN

Ø33
Shelf & Joinery Lights



cutout :33mm



Fixed Optic





True non-intrusive-in lighting solutions to integrate lighting with architecture

Matt White

Matt Black

IP Rating:	IP20
Optics:	15°/25°/30°/50°
UGR:	<17
CRI:	92Ra
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K/3000K
Typical Source Efficacy (lm/W):	103
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning:	2 Step MacAdams
Driver Input:	AC220-240V 50/60Hz
Electrical (System W):	DC 3V 300mA 1.1W DC 3V 650mA 2.4W
Ambient temp:	-20 ℃ to 25 ℃
Class :	III





DuraGreen project:
Curio Hotel

Code example:

MFL 33 1.1W - 30 N 15- W
MFL/ fixed
33/ cutout 33mm
1.1W / system power
30 / 3000K
N / non dim
15/ beam angle 15°
W/ white bezel



W system	lm system	optics	code
1.1W	68	15°	MFL331.1W/S-30NL15-W
1.1W	79	25°	MFL331.1W/S-30NL25-W
1.1W	85	30°	MFL331.1W/S-30NL30-W
1.1W	82	50°	MFL331.1W/S-30NL50-W



W system	lm system	optics	code
2.4W	148	15°	MFL332.4W/S-30NL15-W
2.4W	157	25°	MFL332.4W/S-30NL25-W
2.4W	179	30°	MFL332.4W/S-30NL30-W
2.4W	162	50°	MFL332.4W/S-30NL50-W